





**CUSTOMER SPECIFICATION #6981 Brawler II™**

<b>Product Nomenclature</b>	<b>Manufacturing Glove Code:</b> 6981 <b>Manufacturing Glove Name:</b> Brawler II™
<b>Product Description</b>	 <p><b>Product Class:</b> Supported Nitrile Gloves  <b>Liner Composition:</b> 100% Cotton Interlock  <b>Coating Composition:</b> Acrylonitrile Butadiene Nitrile Fully Coated  <b>Sizes:</b> Small - Extra Large  <b>Packaging:</b> 12 pairs/inner polybag, 144 pairs/case  <b>Exterior Finish:</b> Smooth  <b>Cuff Type:</b> Knit Wrist  <b>Overedge:</b> N/A  <b>Overall Length:</b> S (250 mm), M (260 mm), L (270 mm)  <b>Glove Markings:</b> Brawler II™, CE Pictogram, CE Score, Size Reference, Sanitized® Logo</p>
<b>Characteristics &amp; Applications</b>	 <ul style="list-style-type: none"> <li>• Medium Weight Nitrile for Abrasion, Puncture, Cut and Snag Resistance</li> <li>• Chemical Splash Protection</li> <li>• Excellent Protection against Oils &amp; Greases</li> <li>• Interlock 100% Cotton Fabric for all-day comfort and perspiration absorption</li> <li>• Treated with Sanitized® Anti-bacterial Agent that prevents bacterial and fungal growth. This treatment extends the life of the glove by eliminating odors.</li> <li>• Safe For Food Contact Applications</li> <li>• Applications: Oil &amp; Gas Refining, Metal Fabrication, Mining, Handling Castings and Cores, Leather Glove Replacement</li> </ul>
<b>Typical Performance Values</b>	<b>Thickness:</b> 0.45 mm (+/- .165 mm) <b>Abrasion Resistance:</b> EN388 Level 4 <b>Cut Resistance:</b> EN388 Level 1 <b>Tear Resistance:</b> EN388 Level 1 <b>Puncture Resistance:</b> EN388 Level 1
<b>Quality</b>	Produced in an ISO 9001: 2000 Certified Facility
<b>Shelf Life</b>	Five Years
<b>Country of Origin</b>	India
<b>Originator</b>	Scott M. Laxton/VP Marketing
<b>Date</b>	March 24, 2014

**Corporate Headquarters**  
 4025 Viscount Avenue  
 Memphis, TN. 38118  
 Phone 901-458-5030  
 Fax 901-458-3343



**West Coast Office:**  
 4451 Eucalyptus Avenue  
 Chino, CA 91710  
 Phone 909.590.2679  
 Fax 909.590.3130